Index No. _____

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

SW Corner of Section 15, Township T101N Range R15W, 5th P.M.

STATE OF MINNESOTA, County of MOWER


At the corner location shown on the sketch

☐ On 09/07/1994 (DATE) found a POINTED STONE OVER CONC. MON.

☒ left monument as found, ☐ lowered monument, ☐ removed monument (explain)

☐ On 09/07/1994 (DATE) placed a CAST IRON MONUMENT OVER MON. FOUND

SKETCH OF REFERENCE TIES



JONES, HAUGH & SMITH INC
Civil Engineers & Land Surveyors
Albert Lea, Minnesota

BOOK 88 PAGE 53

Statement of evidence relative to this corner location is on back of page.

I hereby certify that this document and the data contained herein were prepared by me or under my direct supervision.

[signature] 8-7-95
SIGNATURE DATE

Registration No. 13807

☒ Land Surveyor, ☐ Professional Engineer

☐ County Surveyor, ☐ County Engineer

OFFICE OF THE COUNTY RECORDER
County of Mower

I hereby certify that this document was filed in the County Rec. office at 4 p .M. on the 8 day of Aug A.D., 1995

COUNTY RECORDER Charles Engen
By Susan M Davis, Deputy
DOCUMENT NO. 438490

M.H.D. FORM NO. 2105

BK 88 Misc Pg 53

SW Cor SEC 15-101-15

This corner was originally established by Deputy Surveyor John Quigley of the U.S. General Land Office in 1853. The government notes show a wood post was set with a mound of earth and trench.

The following were contacted for section corner information.

Mower County Highway Dept.
Mower County Recorder
Zenk Engineering
Tucker Land Surveying

No record of this corner was obtained from the above mentioned offices.

1994 Jones Haugh and Smith crew, under direction of John Schulte, Mower County Surveyor RLS 13807, dug with county backhoe at CL CL twp. road and CSAH 9. Uncovered an 18" X 10" stone point 3.5' deep above a conc. monument. The stone and conc. mon. were accepted as a perpetuation of the original PLS corner and a CIM was placed over the stone at the road surface.

The monument fit occupation and road centerlines within the section and is accepted as best evidence of a perpetuation of the original public land survey corner.

For electronic survey data and analysis, contact the firm of Jones, Haugh and Smith Inc.