Index No. p76 11 Q' 20

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

S1/4 Corner of Section 20, Township 102N, Range 17W, 5TH P.M.

STATE OF MINNESOTA, County of MOWER


At the corner location shown on the sketch:

☐ On 4-29-92 (DATE) found a ½"Ø X 30"LONG IRON

☐ left monument as found, ☐ lowered monument, ☐ removed monument (explain)

☐ On 4-29-92 (DATE) placed a =⅝"ø x 16" iron stake monument (Capped RLS 13807)

SKETCH OF REFERENCE TIES



JONES, HAUGH & SMITH INC.
Civil Engineers & Land Surveyors
Albert Lea, Minnesota

Statement of evidence relative to this corner location is on back of page.

I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision.

SIGNATURE 11-24-92 DATE

Registration No. 13807

☐ Land Surveyor, ☐ Professional Engineer

☑ County Surveyor, ☐ County Engineer

OFFICE OF THE COUNTY RECORDER
County of _____

I hereby certify that this document was filed in the County Rec. office at _____ .M. on the ____ day of _____ A.D., 19__

COUNTY RECORDER _____

By _____, Deputy

DOCUMENT NO. _____

M.H.D. FORM NO. 2105

STATEMENT OF EVIDENCE

S 1/4 corner Section 20-102-17

This corner was originally established by Deputy Surveyor William I. Anderson of the U.S. General Land Office in 1854. The government notes show a wood post was set with a mound of earth and trench. The following tie was taken:

10" Burr Oak	S 23° W	223 links (147.18 ft)
11" Burr Oak	N 75° W	215 links (141.90 ft)

The following were contacted for section corner information:

Mower County Highway Department
Mower County Recorder
Zenk Engineering
Tucker Land Surveying

The following information was obtained to support evidence of a perpetuation of the original public land survey corner.

1884 Clausen's field notes indicate a government post at the S 1/4 corner.

1992 Jones, Haugh & Smith Inc crew, under the direction of John H. Schulte IV, dug with the county backhoe and uncovered a 1/2" diameter x 30" long iron, five inches deep. Continued digging and found no further evidence. Accepted iron as best evidence and set capped RLS No. 13807 iron, four inches under road surface.

The monument fits occupation and road centerlines within the section and is accepted as best evidence of a perpetuation of the original public land survey corner.

Index No. _____

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

S 1/4 Corner of Section 20, Township 102N, Range 17W, 5th P.M.

STATE OF MINNESOTA, County of MOWER


At the corner location shown on the sketch:

☒ On 4-29-92 (DATE) found a 1/2 ø x 30" long iron

☐ left monument as found, ☐ lowered monument, ☒ removed monument (explain)

☒ On 4-29-92 (DATE) placed a capped RLS 13807 5/8"ø iron at same location

SKETCH OF REFERENCE TIES



JONES, HAUGH & SMITH INC.
Civil Engineers & Land Surveyors
Albert Lea, Minnesota

Statement of evidence relative to this corner location is on back of page.

I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision.

SIGNATURE _____ DATE 5-20-92

Registration No. 13807

☐ Land Surveyor, ☐ Professional Engineer

☑ County Surveyor, ☐ County Engineer

OFFICE OF THE COUNTY RECORDER
County of _____

I hereby certify that this document was filed in the County Rec. office at _____ .M. on the _____ day of _____ A.D., 19 ___

COUNTY RECORDER _____

By _____, Deputy

DOCUMENT NO. _____

M.H.D. FORM NO. 2105

STATEMENT OF EVIDENCE

S 1/4 corner Section 20-102-17

This corner was originally established by Deputy Surveyor Wm. I. Anderson of the U.S. General Land Office in 1854. The government notes show a wood post was set with a mound of earth and trench.

The following were contacted for section corner information:
Mower County Highway Dept
Mower County Recorder's Office
Ray Tucker, RLS

The following information was obtained to support evidence of a perpetuation of the original public land survey corner.

1884 Clausen, County Surveyor, uncovered corner during a survey of the SE 1/4.

1992 Jones, Haugh & Smith Inc crew under the direction of John Schulte RLS, Mower County Surveyor, dug with the County backhoe and uncovered a 1/2" diameter x 30" long pipe. Dug a 5'x12'x4' deep hole and found no further evidence of public land survey corner or a perpetuation thereof. Therefore accepted 1/2" pipe as best evidence and placed a 5/8" diameter iron capped RLS 13807 at same location.

The monument fits occupation and road centerlines within the section and is accepted as best evidence of a perpetuation of the original public land survey corner.