Index No. P35 "E" P108 "M"

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

W1/4 Corner of Section 1, Township 103N Range 18W, 5TH P.M.

STATE OF MINNESOTA, County of MOWER


At the corner location shown on the sketch:

☐ On 10-22-91 (DATE) found a 3/4"ø x 18" PIPE WITH ALUM. CAP

☐ left monument as found, ☐ lowered monument, ☐ removed monument (explain)

☐ On 10-22-91 (DATE) placed a CAST IRON MONUMENT

SKETCH OF REFERENCE TIES



JONES, HAUGH & SMITH INC.
Civil Engineers & Land Surveyors
Albert Lea, Minnesota

Statement of evidence relative to this corner location is on back of page.

I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision.

SIGNATURE 4-30-93 DATE

Registration No. 13807

☐ Land Surveyor, ☐ Professional Engineer

☑ County Surveyor, ☐ County Engineer

OFFICE OF THE COUNTY RECORDER
County of Mower

I hereby certify that this document was filed in the County Rec. office at 3 P.M. on the 4 day of May A.D., 1993

COUNTY RECORDER Shanlon Engel

By Marlene Martin, Deputy

DOCUMENT NO. 420181

Bk MG Misc Pg 328

M.H.D. FORM NO. 2105

BOOK 19 PAGE 328

STATEMENT OF EVIDENCE

W 1/4 corner Section 1-103-18

This corner was originally established by Deputy Surveyor Wm. I. Anderson of the U.S. General Land Office in 1853. The government notes show a wood post was set with a mound of earth and trench. The following tie was taken:

18" Burr Oak S 81 1/2° W 23 links (15.18 ft)

The following were contacted for section corner information:
Mower County Highway Department
Mower County Recorder
Zenk Engineering
Tucker Land Surveying

The following information was obtained to support evidence of a perpetuation of the original public land survey corner.

1884 Clausen, Mower County Surveyor, found a government post at this location.

1991 Jones, Haugh & Smith Inc crew under the direction of John H. Schulte IV, Reg. No. 13807, dug with county backhoe on centerline of north-south road in line with fence running east-west and uncovered a 4" diameter charred wood post three feet long and two feet deep. Therefore we accepted the charred wood post found as the location of the original public land survey corner. We set a 5/8" x 16" iron on the north side of post and a cast iron monument near road surface above post found.

The monument set fits occupation and road centerlines within the section and is accepted as best evidence of a perpetuation of the original public land survey corner.

BOOK 79 PAGE 329

Jones Haugh