Index No. _____

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

N 1/4 Corner of Section 19, Township 103N Range 18W, 5th P.M.

STATE OF MINNESOTA, County of MOWER


At the corner location shown on the sketch

☐ On 04/03/1990 (DATE) found a 1' SQX4' LONG IRON BAR AND SET A 5/8" IRON OVER

☐ left monument as found, ☐ lowered monument, ☐ removed monument (explain)

☐ On 04/03/1996 (DATE) placed a CAST IRON MONUMENT ON 5/8" IRON

SKETCH OF REFERENCE TIES



JONES, HAUGH & SMITH INC
Civil Engineers & Land Surveyors
Albert Lea, Minnesota

Statement of evidence relative to this corner location is on back of page.

I hereby certify that this document and the data contained herein were prepared by me or under my direct supervision.

SIGNATURE _____ DATE 12-31-96

Registration No. 13807

☐ Land Surveyor, ☐ Professional Engineer

☒ County Surveyor, ☐ County Engineer

OFFICE OF THE COUNTY RECORDER
County of Mower

I hereby certify that this document was filed in the County Rec. office at 4 p .M. on the 3 day of Jan A.D., 1997

COUNTY RECORDER Charles J. Enger

By Susan M. Lewis, Deputy

DOCUMENT NO. 450254

M.H.D. FORM NO. 2105 BOOK 93 PAGE 490

BK 93 Page 490 Misc

N 1/4 Cor SEC 19-103-18

This corner was originally established by Deputy Surveyor William Anderson of the U.S. General Land Office in 1854. The government notes show a wood post was set with mound of earth and trench.

The following were contacted for section corner information.

Mower County Highway Dept.
Mower County Recorder
Zenk Engineering
Tucker Land Surveying

No record of this corner was obtained from the above mentioned offices.

1990	Jones Haugh and Smith crew, under direction of John Schulte, Mower County Surveyor RLS 13807, dug with county backhoe at the CL of township road E-W and in line with line fence N-S. Located a 1"x4' long iron 2' below the road surface. Placed a 5/8" iron over iron found capped #13807.
1996	Jones Haugh and Smith crew placed a cast iron monument over 5/8" found.

The monument fits occupation and road centerlines within the section and is accepted as best evidence of a perpetuation of the original public land survey corner.

For electronic survey data and analysis, contact the firm of Jones, Haugh and Smith Inc.