Index No. _____

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

N 1/4 Corner of Section 22, Township T103N Range R18W, 5th P.M.

STATE OF MINNESOTA, County of MOWER


At the corner location shown on the sketch

☐ On 06/08/1994 (DATE) found a FENCE INTERSECTION

☒ left monument as found, ☐ lowered monument, ☐ removed monument (explain)

☐ On 06/08/1994 (DATE) placed a CAST IRON MONUMENT

SKETCH OF REFERENCE TIES



JONES, HAUGH & SMITH INC
Civil Engineers & Land Surveyors
Albert Lea, Minnesota

BOOK 88 PAGE 151

Statement of evidence relative to this corner location is on back of page.

I hereby certify that this document and the data contained herein were prepared by me or under my direct supervision.

SIGNATURE _____ DATE 8-14-95

Registration No. 13807

☐ Land Surveyor, ☐ Professional Engineer

☒ County Surveyor, ☐ County Engineer

OFFICE OF THE COUNTY RECORDER
County of Mower

I hereby certify that this document was filed in the County Rec. office at 3 P.M. on the 21 day of Aug A.D., 19 95

COUNTY RECORDER Charles Engen

By Susan M Davis, Deputy

DOCUMENT NO. 438802

M.H.D. FORM NO. 2105

Book 88 Misc Page 151

N 1/4 Cor SEC 22-103-18

This corner was originally established by Deputy Surveyor William Anderson of the U.S. General Land Office in 1854. The government notes show a wood post was set.

The following were contacted for section corner information.

Mower County Highway Dept.
Mower County Recorder
Zenk Engineering
Tucker Land Surveying

No record of this corner was obtained from the above mentioned offices.

1880 Clausen's field notes indicate he found a government post at this location.

1995 Jones Haugh and Smith crew, under direction of John Schulte, Mower County Surveyor RLS 13807, dug by hand in the area of the corner but found no evidence of the original government post. A CIM was set at the intersection of fences to the north and west. The corner fits the 16th fence in the SW 1/4 of sec 15 and fit the fence at the center of section 15.

The monument fit occupation and road centerlines within the section and is accepted as best evidence of a perpetuation of the original public land survey corner.

For electronic survey data and analysis, contact the firm of Jones, Haugh and Smith Inc.