Index No. _____

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

N1/4 Corner of Section 14, Township 104N Range 18W, 5TH P.M.

STATE OF MINNESOTA, County of MOWER


At the corner location shown on the sketch:

☐ On 10-9-92 (DATE) found a NOTHING

☐ left monument as found, ☐ lowered monument, ☐ removed monument (explain)

☐ On 6-12-93 (DATE) placed a CAST IRON MONUMENT

SKETCH OF REFERENCE TIES



JONES, HAUGH & SMITH INC.
Civil Engineers & Land Surveyors
Albert Lea, Minnesota

Statement of evidence relative to this corner location is on back of page.

I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision.

SIGNATURE _____ DATE 6-10-93

Registration No. 13907

☐ Land Surveyor, ☐ Professional Engineer

☑ County Surveyor, ☐ County Engineer

OFFICE OF THE COUNTY RECORDER
County of Mower

I hereby certify that this document was filed in the County Rec. office at 4 P.M. on the 24 day of June A.D., 1993

COUNTY RECORDER Edward Enger

By Marlene Marten, Deputy

DOCUMENT NO. 421718 Bk 80 Misc Pg. 115

M.H.D. FORM NO. 2105

Bk 80 Page 115

STATEMENT OF EVIDENCE

N 1/4 cor Sec 14-104-18

This corner was originally established by Deputy Surveyor William I. Anderson of the U.S. General Land Office in 1854. The government notes show a wood post was set with a mound of earth and trench.

6" Burr Oak	S 25° W	83 links (54.78 ft)
7" Burr Oak	N 57° E	90 links (59.40 ft)

The following were contacted for section corner information:

Mower County Highway Department
Mower County Recorder
Zenk Engineering
Tucker Land Surveying

The following information was obtained to support evidence of the perpetuation of the original public land survey corner.

1992 Jones, Haugh & Smith crew under the direction of John H. Schulte IV, Reg No. 13807, dug with the County backhoe on centerline of County State Aid Highway No. 1 and in line with line fence running south and found no evidence of a perpetuation of this corner or the original public land survey corner.

1993 Jones, Haugh & Smith Inc crew under the direction of John H. Schulte IV, RLS 13807, set this corner on a straight line between the northwest and northeast corners of Section 14 and also in line with the line fence running south.

The monument set fits occupation lines within the section and is accepted as best evidence of a perpetuation of the original public land survey corner.