Index No. _____

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

NW Corner of Section 31, Township 104N, Range 18W, 5th P.M.

STATE OF MINNESOTA, County of MOWER


At the corner location shown on the sketch:

☐ On 5-1-89 (DATE) found a 3/4"Ø x 18" IRON OVER A 1 3/4"Ø PIPE OVER A STONE.

☐ left monument as found, ☐ lowered monument, ☐ removed monument (explain)

☐ On 5-1-89 (DATE) placed a 5/8"Ø IRON OVER PIPE AND SET CAST IRON MONUMENT.

SKETCH OF REFERENCE TIES



JONES, HAUGH & SMITH INC.
Civil Engineers & Land Surveyors
Albert Lea, Minnesota

Statement of evidence relative to this corner location is on back of page.

I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision.

SIGNATURE _____ DATE 10-11-91

Registration No. 13807

☐ Land Surveyor, ☐ Professional Engineer

☑ County Surveyor, ☐ County Engineer

OFFICE OF THE COUNTY RECORDER
County of _____

I hereby certify that this document was filed in the County Rec. office at _____ .M. on the ____ day of _____ A.D., 19__

COUNTY RECORDER _____

By _____, Deputy

DOCUMENT NO. _____

M.H.D. FORM NO. 2105

STATEMENT OF EVIDENCE

NW cor Sec 31-104-18

This corner was originally established by Deputy Surveyor J.B. Reyman of the U.S. General Land Office in 1854. The government notes show a wood post was set with a mound of earth and trench. The following ties were taken:

10" Burr Oak	N 32° W	73 links (48.18 ft)
8" Burr Oak	S 23° E	703 links (463.98 ft)
6" Burr Oak	N 24° E	111 links (73.26 ft)
12" Burr Oak	S 12° W	91 links (60.06 ft)

The following were contacted for section corner information:
Freeborn County Engineering Department
Freeborn County Recorder's Office
Mower County Engineering Department
Mower County Recorder's Office

1887 Clausen, County Surveyor, notes show a government post inplace.

1952 Book "A" of the Mower County Engineering Department show an iron inplace. The following ties were taken:

50.2' SW to TP	134.0' NW to PP
69.0' NE to Maple tree	53.1' SE to TP

1954 Freeborn County notes show a pipe inplace. The following ties were taken:

Mower County Road sign (C-13)	SE	71.3'
Spk & W in REA pole	NNE	68.9'
SW cor School	NE	130.5'

1962 George Murphy, County employee, uncovered corner. The following ties were taken:

Spk & W in PP	68.9' NE
Spk & W in TP	60.0' SW
Face of tele stand pipe	56.3' SE

1989 Jones, Haugh & Smith Inc crew under the direction of John Schulte, Freeborn County Surveyor, dug with the County backhoe on centerline centerline of north-south-east-west roads. Uncovered a 3/4" diameter x 18" iron 0.5' deep over a 1 3/4" diameter bent pipe. Using a tile probe found pipe to be over a stone 3 feet below road surface. Set a 5/8" diameter iron over pipe and a cast iron monument at surface.

The monument fits occupation and road centerlines within the section and is accepted as best evidence of a perpetuation of the original public land survey corner.