Index No. _____

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

NW Corner of Section 36, Township 103N, Range 17W, 5th P.M.

STATE OF MINNESOTA, County of MOWER


At the corner location shown on the sketch:

☒ On 5-29-91 (DATE) found a 3/4"Ø x 12" iron over a 1/2"Ø x 24" iron on the south side of a pointed field stone.

☐ left monument as found, ☐ lowered monument, ☐ removed monument (explain)

☒ On 5-29-91 (DATE) placed a cast iron monument over pointed stone.

SKETCH OF REFERENCE TIES



JONES, HAUGH & SMITH INC.
Civil Engineers & Land Surveyors
Albert Lea, Minnesota

Statement of evidence relative to this corner location is on back of page.

I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision.

SIGNATURE _____ DATE 6-5-91

Registration No. 13807

☒ Land Surveyor, ☐ Professional Engineer

☐ County Surveyor, ☐ County Engineer

OFFICE OF THE COUNTY RECORDER

County of _____

I hereby certify that this document was filed in the County Rec. office at _____ .M. on the _____ day of _____ A.D., 19__

COUNTY RECORDER _____

By _____, Deputy

DOCUMENT NO. _____

M.H.D. FORM NO. 2105

STATEMENT OF EVIDENCE

NW corner Section 36-103-17

This corner was originally established by Deputy Surveyor William I. Anderson of the U.S. General Land Office in 1853. The government notes show a charred stake was set with a mound of earth and trench.

The following were contacted for section corner information:
Mower County Highway Department
Mower County Recorder
Zenk Engineering
Tucker Land Surveying

The following information was obtained to support evidence of a perpetuation of the original public land survey corner.

1940 Recorded in "A" in the office of the County Engineer it shows a 1 1/4 inch iron bar on the north side of a stone and ties were taken.

1986 Ray Tucker, RLS 15471, uncovered a 1 1/4 inch iron on the west side of the stake. The monument was left as found and a stone was set with a 1/2 inch diameter iron re-bar over stake capped RLS 15471.

1991 Jones, Haugh & Smith Inc dug with the County backhoe for grading project SAP 50-619-15 and uncovered a 3/4 inch diameter iron over a 1/2" X 24" iron re-bar on the south side of a pointed nigger head and the remains of the old wood stake was found around a 1/2" diameter iron. Left the monument as found and set a cast iron monument over a 1/2" diameter iron on the surface.

The monument fits occupation and road centerlines within the section and is accepted as best evidence of a perpetuation of the original public land survey corner.

1997 Re-set