NE cor SEC. 21-103-15

12-30-98 Cloudy 0°F HLS JPA

7-28-1853 JOHN Quigley, deputy surveyor set post in a mound for the corner during the original Public Land Survey.

Oct. 2-1982 MN. DEPARTMENT TRANS. EXCAVATED AN AREA 6'×12'×6' DEEP CENTERED ON THE OCCUPATION LINES. AN OLD ROAD SURFACE WAS FOUND 3' DOWN. AN 8" SPK. WAS FOUND 1' BELOW THE OLD ROADBED ON THE FENCE LINE & CENTER of Rd.

AN ANALYSIS of the SURVEY DATA & adjacent LANDOWNERS STATEMENT INDICATES that the old SPIKE & occupation LINES IS THE BEST EVIDENCE of the OBLITERATED position of the LAND CORNER & HAVE BEEN for OVER 50 YEARS. This position is therefore ACCEPTED AS MARKING the public LAND SURVEY CORNER

8-2-06 FOUND CIM & SHOT w/GPS.

12-30-98 THS CREW UNCOVERED CORNER & ONLY ONE TIE WAS LEFT, NAIL & DISK IN DP. 64.97 — FOUND BROKEN off CIM 1.4"± DEEP — SET NEW CIM OVER .40'± BELOW GRADE SURFACE.

